Specifications for imageCLASS LBP6030B



Print			
Printing Method	Monochrome Laser Beam Printing		
Print Speed	A4:	Up to 18ppm	
	Letter:	Up to 19ppm	
Print Resolution	600 x 600dpi		
Print Quality with Image Refinement Quality	2400 (equivalent) × 600dpi		
Warm-Up Time (From Power On)	10secs. or less		
First Printout Time (FPOT)	Approx. 7.8secs.		
Recovery Time (From Sleep Mode)	Approx. 1secs.		
Print Language	UFR II LT		
Paper Handling			
Paper Input (Standard)	150 sheets (based on 80g/m ²)		
Paper Output	100 sheets (face down) (based on 80g/m ²)		
Paper Size	A4, B5, A5, Legal* ¹ , Letter, Executive, 16K, Envelope COM10,		

	Envelope Monarch, Envelope C5, Envelope DL Custom: Width 76.2 to 215.9mm x Length 188 to 355.6mm			
Paper Weight	60 to 163g/m ²			
Paper Type	Plain paper, Heavy Paper, Transparency, Label, Envelope.			
Connectivity and Software				
USB Interface	USB 2.0 High Speed			
Compatible Operating Systems* ²	Win 8.1 (32 / 64bit), Win 8 (32 / 64bit), Windows 7 (32 / 64-bit), Windows Vista (32 / 64-bit), Windows XP (32 / 64-bit), Windows Server 2012 (32 / 64bit), Windows Server 2012 R2 (64 bit), Windows Server 2008 (32 / 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (32 / 64bit), Windows Server 2003 (32 / 64bit), Mac OS 10.6.x~10.9*3, Linux*3, Citrix			
General Specification				
Operation Panel	2 LED Indicators, 2 Operation Key			
Device Memory	32MB			
Dimensions (W x D x H)	364 x 249 x 199mm			
Weight	Approx. 5.0kg (Without Cartridge)			
Noise Level* ⁴	During Operation:	Sound Power Level:	6.53B or less	
		Sound Pressure Level:	49.3dB	
	During Standby:	Sound Power Level:	Inaudible*5	
		Sound Pressure Level:	Inaudible*5	
Maximum Power Consumption	840W or less			
Average Power Consumption	During Operation:	Approx. 320W		
	During Standby:	Approx. 1.8W (USB connection)		
	During Sleep:	Approx. 0.8W (USB connection)		
Energy Star TEC (Typical Electricity Consumption)	0.48kWh/week			
Operating Environment	Temperature:	10 to 30°C		
	Humidity:	20% to 80% RH	20% to 80% RH (no condensation)	

Power Requirement	220 - 240V (±10%), 50 / 60Hz (±2Hz)		
Toner Cartridge* ⁶	Cartridge 925:	1,600 pages	
Monthly Duty Cycle* ⁷	Up to 5,000 pages		
Recommended Monthly Print Volume	200 - 800 pages		

*4 Tested in accordance to ISO 7779 and declared per ISO 9296

*6 Toner cartridge yield is in accordance with ISO/IEC 19752

P.O.Box CT10766, Cantonments-Accra. No.25 Yama Plaza, Block One-3rd Floor-Apartment Seven. Kingsby Roundabout-Christ Home Avenue, Achimota-AccraCall Deus on Toll-free: 0800666000 DEUS.COM.GH

^{*1} Legal refers to paper measuring 215.9 x 55.6mm (8.5 x 14 inches)
*2 Check <u>www.canon-asia.com</u> for the latest printer driver.
*3 The latest drivers for Mac OS and Linux can be downloaded from <u>www.canon-asia.com</u> when available.

^{*&}lt;sup>5</sup> "Inaudible" means each sound pressure level at bystander's position is less than ISO 7779 absolute criteria

^{*7} Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser devices, and does not refer to actual maximum image output per month